



Analog I/O Modules (Input)

GE offers easy-to-use analog modules and HART analog modules for control processes such as flow, temperature and pressure.

	IC694ALG220	IC694ALG221	IC694ALG222	IC694ALG223
	PACSystems RX3i Analog Input, Voltage, 4 Channel	PACSystems RX3i Analog Input, Current, 4 Channel	PACSystems RX3i Analog Input, Voltage, High Density (16 Channel)	PACSystems RX3i Analog Input, Current, High Density (16 Channel)
Product Name				
Lifecycle Status	Active	Active	Active	Active
Module Type	Analog Input	Analog Input	Analog Input	Analog Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Range	-10 V to +10 V	4-20 mA, 0-20 mA	-10 V to ±10 V, 0 to 10 V	0-20 mA, 4-20 mA
HART Support	N/A	N/A	N/A	N/A
Channel-to-Channel Isolation	N/A	N/A	N/A	N/A
Number of Channels	4	4	1	16
Update Rate	4 ms all channels	2 ms all channels	13 ms all channels	13 ms all Channels
Resolution	12 bit; 5 mV/20 µA/bit	12 bit; 0-20 mA, 5 µA/bit; 4-20 mA, 4 µA/bit	12 bit; ±10 V, 5 mV/20 µA/bit; 0-10 V, 5 mV/20 µA/bit	12 bit; 0-20 mA, 5 µA/bit; 4-20 mA, 4 µA/bit; 4-20 mA Enhanced, 5µA/bit
Accuracy	±10 mV/40µA at 25°C (77°F)	0.1 % full scale	0.25% at 25°C (77°F)	0.25% at 25°C (77°F)
Input Impedance	>9 Megohms	250 ohms	250 ohms	250 ohms
Input Filter Response	17 Hz	325 Hz	200 Hz	200 Hz
Notch Filter	N/A	N/A	N/A	N/A
Diagnostics	N/A	N/A	N/A	N/A
Internal Power Used	27 mA @ 5 VDC; 98 mA @ 24 VDC Isolated	25 mA @ 5 VDC; 100 mA @ 24 VDC Isolated	112 mA @ 5 VDC; 4150 mA- User Supplied 24 VDC	120 mA @ 5 VDC; 65 mA-User Supplied 24 VDC
External Power Requirement	N/A	N/A	N/A	N/A
Connector Type	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.