



Discrete I/O Modules (Output)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL350	IC694MDL732	IC694MDL734	IC694MDL740
Product Name	PACSystems RX3i AC Voltage Output Module, 120/240 VAC Isolated, 2A, 16 Point Output	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic, 0.5A, 8 Point Output	PACSystems RX3i DC Voltage Output Module, 125 VDC Pos/Neg Logic, 6 Point Output	PACSystems RX3i DC Voltage Output Module, 12/24 VDC Positive Logic, 0.5A, 16 Point Output
Lifecycle Status	Active	Active	Active	Active
Module Type	Discrete Output	Discrete Output	Discrete Output	Discrete Output
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1
Output Voltage Range	74-264 VAC	12-24 VDC	11-150 VDC	12-24 VDC
Number of Points	16	8	6	16
Isolation	Yes	N/A	N/A	N/A
	N/A	N/A	N/A	N/A
Diagnostics				
Load Current per Point	Per Point 2A max. @ 30°C & 1A max. @ 60°C (Linear derating)	0.5 A	1 A	0.5 A
Response Time (ms)	1 on/1/2 cy off	2 on/2 off	7 on/5 off	2 on/2 off
Output Type	Triac	Transistor	Transistor	Transistor
Polarity	N/A	Positive	Positive/Negative	Positive
Points per Common	1	8	1	8
Connector Type	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	110 mA @ 5 VDC	50 mA @ 5 VDC	90 mA @ 5 VDC	110 mA @ 5 VDC