

**SAK Series  
AP SAK4-10**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                                       |
|------------|-------------------------------------------------------|
| Type       | AP SAK4-10                                            |
| Order No.  | <a href="#">0117960000</a>                            |
| Version    | SAK Series, End plate, 1.5 mm, beige, Direct mounting |
| GTIN (EAN) | 4008 19008 1485                                       |
| Qty.       | 20 pc(s).                                             |

**SAK Series**  
**AP SAK4-10**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Width      | 1.5 mm | Width (inches)  | 0.059 inch |
| Height     | 40 mm  | Height (inches) | 1.575 inch |
| Depth      | 36 mm  | Depth (inches)  | 1.417 inch |
| Net weight | 2.31 g |                 |            |

**Temperatures**

|                                  |               |                                  |        |
|----------------------------------|---------------|----------------------------------|--------|
| Storage temperature, max.        | 40 °C         | Storage temperature, min.        | 10 °C  |
| Storage temperature              | 10 °C...40 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 100 °C        |                                  |        |

**Material data**

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | PA 66 | Colour | beige |
| UL 94 flammability rating | V-2   |        |       |

**System specifications**

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

**Additional technical data**

|                     |                 |         |     |
|---------------------|-----------------|---------|-----|
| Installation advice | Direct mounting | Snap-on | Yes |
|---------------------|-----------------|---------|-----|

**Classifications**

|            |             |             |             |
|------------|-------------|-------------|-------------|
| ETIM 6.0   | EC000886    | ETIM 7.0    | EC000886    |
| eClass 9.1 | 27-14-11-33 | eClass 10.0 | 27-14-11-33 |
| UNSPSC     | 30-21-18-27 |             |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| Engineering Data   | <a href="#">EPLAN, WSCAD</a>                                     |
| Engineering Data   | <a href="#">03342_AP_SAK4-10_DXF.dxf</a><br><a href="#">STEP</a> |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a>                  |